

# UNAPPROVED



[www.picotech.com](http://www.picotech.com)

**UK headquarters**

James House  
Colmworth Business Park  
Eaton Socon  
Cambridgeshire  
PE19 8YP  
United Kingdom

Tel: + 44 (0) 1480 396395  
Fax: + 44 (0) 1480 396296  
[support@picotech.com](mailto:support@picotech.com)

**North America regional office**

320 N Glenwood Blvd.  
Tyler  
TX 75702  
United States of America

Tel: +1 800 591 2796  
Fax: +1 620 272 0981  
[support@picotech.com](mailto:support@picotech.com)

**Asia-Pacific regional office**

Pico Technology  
Room 2252, 22/F, Centro  
568 Hengfeng Road  
Zhabei District  
Shanghai 200070  
PR China

Tel: +86 (0) 21 2226-5152  
[pico.china@picotech.com](mailto:pico.china@picotech.com)

To whom it may concern:

The PicoVNA 106 Vector Network Analyzer is a USB-controlled instrument and contains the following memory devices:

<b>Memory device</b>	<b>Volatility</b>	<b>Usage</b>
1 x 32 kB serial EEPROM	Non-volatile	Configuration and calibration information programmed by Pico Technology
512 kB dsPIC33EP512MU810 microcontroller	Non-volatile	Firmware
2 x 64 B ATF1504ASVL programmable logic device	Non-volatile	Glue logic
1 x 512 kB CY62157EV30LL memory device	Volatile	Configuration information programmed by the user

Volatile memory loses its contents when the device is powered off while non-volatile memory retains its contents when the device is powered off.

In order to clear user data or settings from these instruments, simply disconnect the USB cable and the external power supply lead. No user data or settings are saved within the instrument when these two cables are removed.

Please contact Pico Technology Ltd. at the above contact points if further detail is required.